

INVENTER – 3D PRINTER

Give your design a real touch

New Generation Smart Dual Extruder 3D Printer

Physical Characteristics:

Build envelope (volume):

230 x 150 x 160mm (9.0" X 5.9" X 6.2")

Layer thickness (Z-resolution):

0.1-0.5mm

Build speed: 40-100mm/s

Printing Material: 1.75mm ABS /PLA/PVA

Printer Size: 565 x 430 x 453 mm

(22.24" x 16.9" x 17.8")

Printer Weight: 18.0 kg (39.6 lbs)

Connectivity: Wi-Fi, USB Cable, SD Card.

Software: FlashPrint

Extruder: Dual

Nozzle Diameter: 0.4mm



Specifications:

Power Requirement: 100-240 V, ~2amps, 50-60 Hz, 300 W

Input Format: STL / OBJ

Operating Systems: Windows, OSX, Mac

Positioning Precision: 0.0025mm on Z axis, 0.011mm on XY axes

Operation requirement:

Extruder Temp.: Max. 240 °C

Heat Bed Temp.: Max. 115°C

Power Requirement: 100-240 V, ~2amps, 50-60 Hz, 300 W

Why from Us:

- Local Warranty & Technical Support
- 1 Spool of ABS/PLA Filament.