

FLASHFORGE ADVENTURER-3 – 3D PRINTER

Give your design a real touch

New Generation Smart Single Extruder 3D Printer

Physical Characteristics:

Build envelope (volume):

150 x 150 x 150mm (5.5" X 5.5" X 5.5")

Layer thickness (Z-resolution):

0.1-0.4mm

Build speed: 40-100mm/s

Printing Material: 1.75mm

ABS/PLA/HIPS/PVA/Flexible Filament

Printer Size: 388x380x405mm

Printer Weight: 19.85 kg

Connectivity: USB Cable, SD Card.

Software: FlashPrint

Extruder: Single

Nozzle Diameter: 0.4mm



Specifications:

Power Requirement: 100-240 V, ~2amps, 50-60 Hz, 350 W

Input Format: STL / OBJ

Operating Systems: Windows, OSX, Mac

Positioning Precision: 0.0025mm on Z axis, 0.011mm on XY axes

Operation requirement:

Extruder Temp.: Max. 220 °C

Heat Bed Temp.: Max. 110°C

Power Requirement: 100-240 V, ~2amps, 50-60 Hz, 350 W

Why from Us:

- Local Warranty & Technical Support
- 2*Filament(0.6KG) Spool of ABS/PLA Filament.

System requirement:

- i5 Processor, 2GB Graphics Card, OpenGL2.1

3D Spectra Technologies LLP

Flat No. 3, Jansunder Co- Op Hsg Soc A- Wing,

Above Taware Bakery, Taware Colony,

Off Satara Road, Parvati Pune-411009

P: +91 20 24218090

M: +91 9623693654

E: sales@3dspectratech.com W: www.3dspectratech.com