

FLASHFORGE GUIDER 2- 3D PRINTER

Give your design a real touch

Physical Characteristics:

Build envelope (volume):

280L X 250 W X 300 H mm (11.2" X
9.8" X 11.8")

Layer thickness (Z-resolution):

0.1-0.5mm

Build speed: 30-100mm/s

Printing Material: PLA, ABS

Printer Weight: 20 kg.

Connectivity: USB Cable, USB Stick.

Software: Flashprint

Extruder: Single



Specifications:

Power Requirement: 100-240V AC Input 300W

Input Format: STL/OBJ/GX/G

Operating Systems: Windows XP, Vista, 7, 8, 8.1 (32/64bit) & Mac OSX

Positioning Precision: 0.0025mm on Z axis, 0.011mm on XY axes

Operation requirement:

Extruder Temp.: Max. 240 °C

Power Requirement: 100-240V AC Input 300V

System requirement:

i5 Processor, 2GB Graphics Card, OpenGL2.1

Why from Us:

- Local Warranty & Technical Support
- 1 Spool of ABS/PLA Filament

3D Spectra Technologies LLP

Flat No. 3, Punyanagari Co- Op Hsg Soc D- Wing,

Near Amrapali Petrol pump,

Off Bibwewadi Road, Bibwewadi Pune-411037

P: +91 20 24218090

M: +91 9623693654

E: sales@3dspectratech.com

W: www.3dspectratech.com