

FLASHFORGE GUIDER 2S- 3D PRINTER

Give your design a real touch

Physical Characteristics:

Build envelope (volume):

280L X 250 W X 300 H mm (11.2" X 9.8" X 11.8")

Layer thickness (Z-resolution):0.1-0.5mm

Build speed: 30-100mm/s

Printing Material: ABS, PLA, PETG, HIPS,
Flexible Filament (TPU)

Printer Weight: 30 kg.

Connectivity: USB Cable, USB Stick, Wi-Fi, Ethernet

Software: FlashPrint

Extruder: Single



Specifications:

Power Requirement: 100-240V AC Input 500W

Input Format: STL/OBJ/GX/G

Operating Systems: Windows XP, Vista, 7, 8, 8.1 (32/64bit) & Mac OSX

Printing Accuracy: ± 0.2 mm

Additional Features:

Built in camera for monitoring: Yes

Print recovery: Yes

Filament sensor: Yes

Filter Screen: Yes

Operation requirement:

Extruder Temp.: Max. 240 °C

Power Requirement: 100-240V AC Input 500W

System requirement:

i5 Processor, 2GB Graphics Card, OpenGL2.1

Why from Us:

- Local Warranty & Technical Support
- 1 Spool of ABS/PLA Filament

3D Spectra Technologies LLP

Flat No. 3, Punyanagari Co- Op Hsg Soc D- Wing,
Near Amrapali Petrol pump,

Off Bibwewadi Road, Bibwewadi Pune-411037

P: +91 20 24218090

M: +91 9623693654

E: sales@3dspectratech.com

W: www.3dspectratech.com